

# SafeFAST Light

Class II Microbiological Safety Cabinets



to EN 12469:2000

of lack of space!

## **DIMENSIONS** (wxdxh)

- useful: 732x380x600 mm
- ✓ overall: 830x650x980 mm



STANDARD ALUMINIUM **NIGHT-DOOR PANEL AND ELECTRICAL OUTLET** 



AISI 304L STAINLESS STEEL WORK SURFACE AND BACK PANEL, **GLASS SIDEWALLS** 





HINGED FRONTAL **GLASS SCREEN** WITH SPRINGS

# **TECHNICAL SPECIFICATIONS**

- ✓ Inflow: 0.45 m/s
- Downflow: 0.35 m/s
- ✓ Noise: < 53,5 dB(A)
  </p> according to EN12469
- ✓ Lighting: > 800 lux
- ✓ Vibrations: < 0.004 mm RMS
  </p>
- Working aperture: 200 mm (Maximum aperture: 440 mm)
- Performances in accordance to EN12469:2000
- Electrical outlet
- Provisions for taps installation



Eco Controlling System® microprocessor based

monitoring system with digital visualization of the following parameters:

- LAF and air flow barrier velocity
- Downflow and exhaust flow rate
- Residual lifetime of HEPA filters and UV lamp
- Display of total time of cabinet operation
- Display of power rating factor of motor blower
- Alarms for:
  - downflow or inflow velocity out of correct range
  - HEPA filters clogged
  - UV lamp worn-out (if installed)
  - signal of other possible malfunction and relevant remedies
  - blackout
  - front window out of the working position

Digital display available in English, French, German, Italian, Spanish, Polish, Hungarian, Romanian and Czech languages!

### **ACCESSORIES**

- Additional electrical power socket
- Gas/Vacuum tap(s)
- Exhaust hard duct connection
- Volt free contact
- Arm rest
- Epoxy powder painted supporting stand
- UV light



#### Faster S.r.l.

Via R. Merendi, 22 20010 Cornaredo (MI) Italy Tel +39 02 93 991 92 Fax +39 02 93 991 608 www.faster-air.com info@faster.dgroup.it













